

Serial No. 10/847,788  
Examiner: FLEMING, Faye M.  
Art Unit 3818

Page 2 of 7

### Amendments to the Specification

Please replace paragraph [0016] with the following amended paragraph:

[0016] One additional aspect of the present invention provides an ATV with a frame, and only four wheels suspended from the frame. Two of the wheels are front wheels and two of the wheels are rear wheels. The front wheels define a front axis and the rear wheels define a rear axis. The front axis and the rear axis define a wheelbase of greater than 51 inches, and each wheel includes an ATV-type tire, i.e. a low-pressure balloon tire having an air pressure of less than 1 kg/cm<sup>2</sup>. The ATV has two shock absorbers connected to the frame. The shock absorbers are associated with the rear wheels. A power unit for driving at least one of the wheels is disposed on the frame. The ATV also has a straddle-type seat disposed on the frame, and handlebars for steering at least one of the wheels disposed on the frame.

**BEST AVAILABLE COPY**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**